

Project:
Type:
Date:
Product Code:
Approval:



BLSDI

This superior-grade LED decorative retail fixture is ideal for indoor use, where energy efficiency, performance and ease of maintenance is essential. Its rugged design and superior light paths make it an ideal fixture for retail applications.

FEATURES

- Lensing provides dust protection, and uniform light while maximizing the total generated light efficacy
- L70 of 100,000 hours
- 0 10V dimming standard

OPTIONS

- Available in 3000K, 3500K, 4000K, 5000K, and 6500K
- 90 CRI available

OPERATING TEMPERATURE

-20°C to 40°C

APPLICATIONS

- Offices
- Retail Stores

WARRANTY

Standard 5 year system, and 10 year LED warranty

OPTICS

High-efficiency diffuser maximizes light distribution while providing diffusion of LED point sources and reducing glare

ELECTRICAL

All components are UL listed or recognized. This fixture is available in 120-277V and 347V

MOUNTING

Holes provided for v-hangers, s-hook chain-mounting or aircraft cable. Optional pendant mounting and surface mounting is available.


CONSTRUCTION


- Cold rolled steel fixture components are precision bent for added strength and rigidity
- Steel end caps for added rigidity
- Powder coated for a clean look and durable finish


APPROVALS

- · Dry and Damp Environment Rated
- ETL Listed
- DLC Listed

PRODUCT DIMENSIONS













BLSDI

PRODUCT KEY

Fixture Type	Number of Bars	Lumen Output	CRI	Color Temp	Driver Voltage	Options	i	
BLSDI		· L	-		-	- L18		
	3	3 4 5 6 7	8 - 80 CRI 9 - 90 CRI	30 - 3000 K 35 - 3500 K 40 - 4000 K 50 - 5000 K 65 - 6500 K	UNV - 120-277V 347 - 347V	Lenses L0 L18 Cords W3xx	- No Lens - Frosted Acryli	
	4	4 5 6 7 8 9				W4xx W** XX 06 10 15 20 Example: W3	- 16/3 Black Co - Other Options Cord Length 6 Ft 10 Ft 15 Ft 20 Ft	

Mounting

M6xx	- Aircraft Cable Loop Kits
M**	- Other Options Available

XX	Aircraft Length
05	5 Ft
10	10 Ft
15	15 Ft
20	20 Ft

Example: M610 - 10 foot aircraft cables loop kit

Controls

B11 - 0-10V Dimming Leads

Colours

Blank - White Low-Gloss, Matte Finish
C5 - Black Low-Gloss, Matte Finish
C** - Other Options Available

WATTAGE CHART

BLSDI DLC Wattage Chart							
Number of Bars			Fixture Lu en Wattage per ut				
3	4	4236	31.4	135.1			



^{** -} Consult BJ Take for more fixture options

xx - Specify Length

^{1 -} Custom cord lengths are available