

## LINEAR CONVECTOR PRO BASEBOARD HEATER

The Linear convector baseboard heater is designed to provide safe, convenient comfort. All aspects of installation and performance are optimized for simplicity and reliability, while the benchmark Dimplex styling is maintained.



### BENEFITS

- 10-20% shorter than conventional baseboards
- Quick and easy installation with rear junction box and easy-to-remove front covers
- Ships ready to install with front cover removed
- Shark-fin heating element blade design improves heat transfer, provides quiet operation, and extends product life
- Use with wall, or top-mounted, built-in thermostat (not included)
- Built-in wire way along the full length of the unit allows you to run wire to opposite end of heater if necessary

### APPLICATIONS

All Residential Applications | Commercial Offices | Lobbies



### SPECIFICATIONS

Voltage	120V, 208V, 240V/208V, 50/60 Hz, 1-phase
Wattage	Sizes ranging from 500W to 2500W
Color	White
Finish	Powder coating resists fading and abrasion
Construction	22-gauge steel construction Front air intake; top warm air discharge Linear high-limit temperature control with automatic reset
Heating Element	Steel sheathed element provides superior life expectancy
Watt Density	Average standard watt density of 300W/ft (984W/m)
Warranty	10-year element warranty 1-year warranty on complete unit

### BUILT-IN THERMOSTATS

DTK-SP*	Single pole built-in thermostat kit (adjustable)	120-240V, 17A
DTK-DP*	Double pole built-in thermostat (adjustable)	120-240V, 17A

\*Adjustable kits contain white and almond control knobs and hardware.

### ORDERING GUIDE

Cat. No.	Watts	Volts	BTU	Length (mm/in)	Weight (kg/lbs.)
LCM2505W11	500	120	1706	635 / 25	2 / 4.4
LCM2505W21	500	208	1706	635 / 25	2 / 4.4
LCM2505W31	500 / 375	240 / 208	1706 / 1280	635 / 25	2 / 4.4
LCM3007W11	750	120	2559	762 / 30	2.3 / 5
LCM3007W21	750	208	2559	762 / 30	2.3 / 5
LCM3007W31	750 / 563	240 / 208	2559 / 1919	762 / 30	2.3 / 5
LCM4010W11	1000	120	3412	1016 / 40	3.2 / 7.5
LCM4010W21	1000	208	3412	1016 / 40	3.2 / 7.5
LCM4010W31	1000 / 750	240 / 208	3412 / 2559	1016 / 40	3.2 / 7.5
LCM5012W11	1250	120	4265	1270 / 50	3.7 / 8.2
LCM5012W21	1250	208	4265	1270 / 50	3.7 / 8.2
LCM5012W31	1250 / 938	240 / 208	4265 / 3199	1270 / 50	3.7 / 8.2
LCM6015W11	1500	120	5118	1524 / 60	4.4 / 9.7
LCM6015W21	1500	208	5118	1524 / 60	4.4 / 9.7
LCM6015W31	1500 / 1125	240 / 208	5118 / 3839	1524 / 60	4.4 / 9.7
LCM7520W21	2000	208	6824	1905 / 75	5.4 / 11.9
LCM7520W31	2000 / 1500	240 / 208	6824 / 5120	1905 / 75	5.4 / 11.9
LCM9025W21	2500	208	8530	2286 / 90	6.4 / 14.1
LCM9025W31	2500 / 1875	240 / 208	8530 / 6398	2286 / 90	6.4 / 14.1

### DIMENSIONS

