

EMT RYMCO® REAL COLOR®



RYMCO®

CALIDAD 360

- Available in 8 vibrant colors, produced from our standard galvanized EMT. Trade sizes 1/2 -4.
- Don't waste time spray-painting or taping - we have a full rainbow of Color EMT in stock and ready to ship.
- Please note - conduit color is for purposes of identification only. Color shades and tones can vary per piece.
- Freedom Coat in the interior for a better wiring.



RYMCO's Real Color® EMT :

White EMT



- * Blends in light colored areas
- * Open architecture

Green EMT



- * Hospital and Healthcare Areas
- * Nurse Call Stations
- * Critical Circuits

Purple EMT




- * Specialty Wiring Systems
- * Security Systems

Yellow EMT



- * Blends in Dark Colored Areas / Caution Areas
- * Special Equipment

Orange EMT



- * Construction / Research Areas
- * Fiber Optic Systems
- * Auto Repair / Maintenance

Blue EMT



- * Low Voltage Wiring
- * Data Com / Video / Network Security

Pink EMT



- * Hospitals
- * Special occasions

Silver EMT



- * Blends in Light Colored Areas.

Red EMT



- * Emergency Circuits
- * Fire Alarm and Security Systems

Black EMT



- * Blends in Dark Colored Areas

Tubería EMT* UL 797 / Real Color EMT*

Diámetro Nominal Nominal Size		Peso 10 tramos Weight 10 Unit Lengths		Diámetro Externo(1) Outside Diameter(1)		Espesor Nominal (2) Nominal Thickness(2)		Color de cinta Tape Color	Piezas x atado Pieces x bundle	Piezas x paquete Pieces x lift
in.	mm.	lb.	kg.	in.	mm.	in.	mm.			
1/2"	16	30	13.6	0.706	17.93	0.042	1.07	Black	10	700
3/4"	21	46	20.9	0.922	23.42	0.049	1.25	Red	10	500
1"	27	67	30.4	1.163	29.54	0.057	1.45	Blue	10	300
1 1/4"	35	101	45.8	1.510	38.35	0.065	1.65	Red	5	200
1 1/2"	41	116	52.6	1.740	44.20	0.065	1.65	Black	5	150
2"	53	148	67.1	2.197	55.80	0.065	1.65	---	---	120
2 1/2"	63	216	98.0	2.875	73.03	0.072	1.83	---	---	61
3"	78	263	119.3	3.500	88.90	0.072	1.83	---	---	51
3 1/2"	91	349	158.3	4.000	101.60	0.083	2.11	---	---	37
4"	103	393	178.3	4.500	114.30	0.083	2.11	---	---	30

Nota: Tolerancias Aplicables
Note: Applicable Tolerances

* Recubrimiento Híbrido Interior Aislante y Anticorrosivo
* Interior Insulated Coating

Largo/Length: 10 Ft. (3.05m) +/-1/4 in. (+/-6.35mm)
(1) 1/2"-2" +/-0.005 in. (16-53 +/-0.13mm), 2 1/2" +/-0.010 in. (63 +/-0.25mm),
3" +/-0.015 in. (78 +/-0.38mm), 3 1/2"-4" +/-0.020 in. (91-103 +/-0.51mm) (2)
Solo informativo no requerimiento UL. For info. Only not a UL requirement.