

DIVVEE

SPLIT

ENERGY MANAGEMENT SYSTEM

SPECIFICATIONS

CURRENT RATING: 40 AMPS**VOLTAGE:** 240/208 AC VOLTS SINGLE PHASE**CYCLE TIMER FACTORY SETTING:** 2 HOURS**FREQUENCY:** 50-60HZ PHASE**ENCLOSURE:** NEMA 1**AGENCY APPROVAL:** CQAIUS LISTED**BOX DIMENSIONS:** 12"X12"X 6"**KNOCK-OUT DIMENSIONS:** ½", ¾", 1", 1¼", 1½"**WEIGHT:** 10LBS (4.5KG)

Introducing the all new **DIVVEE Split**. This industrial-duty device allows you to seamlessly share power between two EV chargers on an adjustable 2-hour cycle. Beyond EV charging, the DIVVEE Split is certified to manage power for hot tubs, HVAC systems, workshops, and more. By leveraging your existing electrical infrastructure, it eliminates the need for costly panel upgrades, ensuring reliable and efficient power distribution. Enhance your electrical system with the DIVVEE Split and experience advanced energy management tailored to your needs.

LEVEL 2 EV CHARGING NO PANEL UPGRADE 40 AMP CURRENT ANY DEVICE UP TO 240V INDUSTRIAL-DUTY 

MORE FROM LOADSHARE

DIVVEE 40

ENERGY MANAGEMENT SYSTEM

CURRENT RATING: 40 AMPS

RELAY SENSITIVITY: 1 AMP

VOLTAGE: 240/208 AC VOLTS SINGLE PHASE

RELAY RESPONSE TIME: 200MS

FREQUENCY: 50-60HZ PHASE

ENCLOSURE: NEMA 1

AGENCY APPROVAL: CQAIUS LISTED

BOX DIMENSIONS: 12" X 12" X 4"

KNOCK-OUT DIMENSIONS: ½", ¾", 1"

WEIGHT : 8LBS (3.7KG)



DIVVEE 60

ENERGY MANAGEMENT SYSTEM

CURRENT RATING: 60 AMPS

RELAY SENSITIVITY: 2 AMPS

VOLTAGE: 240/208 AC VOLTS SINGLE PHASE

RELAY RESPONSE TIME: 200MS

FREQUENCY: 50-60HZ PHASE

ENCLOSURE: NEMA 1

AGENCY APPROVAL: CQAIUS LISTED

BOX DIMENSIONS: 12" X 12" X 6"

KNOCK-OUT DIMENSIONS: ½", ¾", 1", 1¼", 1½"

WEIGHT : 10LBS (4.5KG)

