

9D Series

3 configurations available in a single product:

- Single, pole splitter: Split of main power input into 4, 6, 10 or 11 outputs
- Multiple, pole splitters: Splitting with increased number of outputs
- Grouping: Combining several inputs to make a single output (eg. solar applications)



Panels for electrical distribution



Control panels






High Current Terminal Blocks

- Nominal current: 80, 125, 175, 250 or 400 A
- SCCR Rating – 100 kA
- Available with 7, 8 or 12 connections (according to type)
- Cable connection capacity up to 185 mm² cross section
- Screw terminals
- 35 mm rail (EN 60715) mount



Approvals (according to type):

9D.01.5.080.0304	9D.01.5.125.0206	9D.01.5.175.0210	9D.01.5.250.0111	9D.01.5.400.0111
• 80 A • 7 connections	• 125 A • 8 connections	• 175 A • 12 connections	• 250 A • 12 connections	• 400 A • 12 connections



INPUT WIRE SPECIFICATION (Solid/Stranded)

Number of input		3	1	2	1	1
Terminal diameter	Ømm	6.6	9.8	11.8	15.3	15.3
Min. wire size	mm ²	2.5	10	10	35	95
	AWG	14	8	6	2	3/0
Max. wire size	mm ²	16	35	70	120	185
	AWG	6	2	2/0	250 Kcmil	400 Kcmil
Wire input stripping length	mm	15	15	15	28	28
Tool		Posidriv - flat screwdriver	Allen Key	Allen Key	Allen Key	Allen Key
Tool dimension	mm	5.5/PZ2	4	5	6	8
Torque	Nm	1.5...2	3.5...5	6...10	19...21	25

OUTPUT WIRE SPECIFICATION (Solid/Stranded)

Number of output		4	1	6	10	2	5	4	2	5	4
Terminal diameter	Ømm	4.5	6.8	6.4	6.4	8.7	6.4	5.7	8.7	6.4	5.7
Min. wire size	mm ²	2.5	6	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5
	AWG	14	10	14	14	14	14	14	14	14	14
Max. wire size	mm ²	6	16	16	16	35	16	10	35	16	10
	AWG	10	6	6	6	2	6	8	2	6	8
Wire input stripping length	mm	11	11	11	11	11	11	11	11	11	11
Tool		Posidriv - flat screwdriver	Allen Key	Posidriv-flat screwdriver	Posidriv - flat screwdriver	Allen Key			Allen Key		
Tool dimension	mm	4/PZ1	3	5.5 PZ2	5.5/PZ2	4	3	3	4	3	3
Torque	Nm	0.8...12	2...3	2...3	2...3	3.5...5	2...3	2...3	3.5...5	2...3	2...3